

## CLAIMS

**I claim:**

1. A method of calibrating a digital image capture device, comprising the steps of:
  - acquiring a test target;
  - determining measurement values from the test target;
  - normalizing the measurement values to a range of 0 to 1;
  - determining white point chromaticity for the digital image capture device;
  - converting the normalized measurement values to the digital image capture device white point chromaticity;
  - capturing raw color values of the test target with the digital image capture device;
  - normalizing the captured raw color values to a range of 0 to 1;
  - regressing the normalized measurement values with the normalized raw color values to determine a first compensation matrix; and
  - verifying a level of color fidelity of the digital image capture device.
2. The method of claim 1, wherein the step of determining measurement values from the test target comprises the step of accepting published measurement values for the test target in a physical color space.
3. The method of claim 1, wherein the step of determining measurement values from the test target comprises the step of measuring the test target with calibrated test equipment in a physical color space.

Sub A1

4. The method of claim 1, wherein the step of converting the normalized measurement values to the digital image capture device white point chromaticity comprises the step of using simplified Bradford white point adaptation equations to bring the normalized measurement values into the capture device color space.

5. The method of claim 1, wherein the step of capturing raw color values of the test target with the digital image capture device comprises the step of disabling any gamma correction function of the capture device prior to capturing raw color values of the test target.

6. The method of claim 1, wherein the step of regressing the normalized measurement values with the normalized raw color values to determine a first compensation matrix comprises the steps of assigning the normalized measurement values from the test target converted to the capture device white point as the dependent data, and assigning the normalized raw color data as the independent data.

7. The method of claim 6, further comprising the step of forcing a y-intercept of the regression to zero.

8. The method of claim 6, wherein the step of regressing is performed on an electronic spreadsheet.

Sub  
A:  
(contd)

9.

~~matrix multiplying the first compensation matrix with the normalized raw color~~

5

checking  $\Delta E^*_{CIE94}$  against a predetermined threshold for acceptable color

10. The method of claim 9, wherein the step of comparing the normalized test

11. The method of claim 9, wherein the step of checking  $\mathfrak{g} \in E^* \text{CIE94}$  against a

12. The method of claim 9, wherein the step of checking  $\Psi_{E^*}^{CIE94}$  against a

downloading the second compensation matrix into the capture device.

5            13.    The method of claim 12, wherein the step of calculating a second compensation matrix comprises the step of translating the first compensation matrix from capture device color space to a device independent color space.

14. The method of claim 1, wherein the step of acquiring a test target  
10 comprises the step of developing a customized test target for a particular application.

15. The method of claim 1, wherein the step of acquiring a test target comprises the step of acquiring a test target with at least six color patches thereon.

15            16.    The method of claim 15, wherein said at least six color patches include a  
white patch, a black patch, a gray patch, and three orthogonal colors.

17. The method of claim 16, wherein the gray patch is in the range of 25% to 75% gray.

18. The method of claim 1, wherein the step of acquiring a test target comprises the step of acquiring a test target whose spectral makeup is representative of the type of material of the objects whose digital images will be captured.

Sub  
A' -  
(contd)

[illegible]

capturing color data from an image;

compensating the normalized color data with a compensation matrix.

20. The method of claim 19, further comprising the step of converting the

21. The method of claim 19, wherein the step of compensating the normalized data with a compensation matrix comprises the step of calibrating the capture through the following steps:

- acquiring a test target;
- determining measurement values from the test target;
- normalizing the measurement values to both black and white;
- determining white point chromaticity for the digital image capture device;
- converting the normalized measurement values to the digital image capture device

capturing raw color values of the test target with the capture device;

normalizing the captured raw color values to both black and white; and

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

regressing the normalized measurement values with the normalized raw color

22. \ The method of claim 21, further comprising the step of verifying a level of

10 23. A digital image capture device, comprising a memory storage element

15            24.    The digital image capture device of claim 23, further comprising

20            25.    The digital image capture device of claim 24, wherein said processing

[illegible]